PRODUCT SPECIFICATIONS

930 Full Body Harness

Product Description

The 900 series can be used in a multitude of applications. The harness is donned by a step-thru procedure that is quick and easy.

Product Features

- Front cross-over style
- 4 point adjustment
- Adjustable shoulder and leg straps
- Chest D-rings for positioning, suspension and rescue
- Lightweight, high strength synthetic webbing

MATERIAL SPECIFICATIONS	
Webbing	1-3/4" polyester webbing, minimum tensile strength 6,000 lbs.
Hardware	D-rings: plated alloy steel proof loaded to 3,600 lbs.
	Min tensile strength 5,000 lbs.
	Mating Buckles: plated alloy steel, min tensile strength 4,000 lbs.
	Friction Buckles: plated alloy steel, min tensile strength 4,000 lbs.

PERFORMANCE SPECIFICATIONS	
ANSI User Capacity	130 to 310 lbs
OSHA User Capacity	400 lbs

RELEVANT STANDARDS	
ANSI	ANSI Z359.1
OSHA	Meets or exceeds all OSHA requirements

SIZES/LENGTHS
XS, S, M, L, XL, 2XL, 3XL

100 N 13th St. • Franklin PA • 16323
877.228.9327 • 814-437-1808
frenchcreekproduction.com

WARNING: Read, understand and follow all labels and instructions prior to use, Inspect before each use. Remove from service if there is evidence of damage or excessive wear

FrenchCreek FALL SAFETY