



All Outlaw series SRL's are part of FrenchCreek's QuickShip service, which means they are eligible for same or next day shipping. Please call for more information.

OUTLAW SRL MODEL SELECTIONS			
Model #	Housing/Swivel Connector*	Lifeline Constituents	Approximate Weight
XR-7W	#354-4 (1" opening steel carabiner)	High Strength Synthetic Webbing	3.5lbs
XR-11G	#354-4 (1" opening steel carabiner)	Galvanized Steel Cable	6lbs
XR-11S	#354-4 (1" opening steel carabiner)	Stainless Steel Cable	6lbs
XR-11T	#354-4 (1" opening steel carabiner)	Technora Rope	6lbs
XR-30G	#354-4 (1" opening steel carabiner)	Galvanized Steel Cable	10lbs
XR-30S	#354-4 (1" opening steel carabiner)	Stainless Steel Cable	10lbs
XR-30T	#354-4 (1" opening steel carabiner)	Technora Rope	10lbs

\*Other housing or swivel connectors may be able upon request

OUTLAW SRL LE MODEL SELECTIONS			
Model #	Housing/Swivel Connector*	Lifeline Constituents	Approximate Weight
XR-20LEG	#354-4 (1" opening steel carabiner)	Galvanized Steel Cable	10lbs
XR-30LEG	#354-4 (1" opening steel carabiner)	Galvanized Steel Cable	13lbs
XR-50LEG	#354-4 (1" opening steel carabiner)	Galvanized Steel Cable	18lbs



**All Outlaw series SRL's include: \***

**#49**

Steel swivel locking snaphook, 3/4" gate  
Proof loaded up to 3,600 lbs.  
Minimum braking load: 5,000 lbs.

**\*XR-7W includes:**

**#Z74**

Steel locking snaphook, 3/4" gate  
Proof loaded up to 3,600 lbs.  
Minimum braking load: 5,000 lbs.



**FrenchCreek**  
**FALL SAFETY**

frenchcreekproduction.com

©2019 FrenchCreek Production Inc.  
100 N. 13th St.  
Franklin, PA 16323

*Please call to locate your nearest distributor*  
**877.228.9327**  
**814.437.1808**

Product descriptions and specifications herein may change without notice.

Outlaw-RevA



**THE OUTLAW**  
**SERIES**



**FrenchCreek**  
**FALL SAFETY**



# THE OUTLAW SERIES - SELF RETRACTING LIFELINES



**Swivel Anchor**  
Swivels 360° to limit line twisting for smooth operation

**Light, Durable Housing**  
High-strength, light weight housing provides excellent durability

**Internal Energy Absorption System**  
Reduces fall arrest forces and minimizes free fall distance should a fall occur.

**Weight Capacity**  
Outlaw series meets:  
ANSI requirement 130-310lbs  
  
OSHA requirement 420lbs or less

**Impact Indicator**  
Locking snap with impact indicator allows for visual inspection of the slightest fall into the unit

**Short Fall Arrest Activation**  
Unit will stop a fall within inches, reducing fall distances and reducing fall arrest forces to 1,800 lb. or less

**Lifeline Constituents**  
Choose the lifeline type to meet the specific needs of your job requirement:  
Galvanized Steel  
Stainless Steel  
Technora® synthetic rope

**Meets or Exceed Industry Standards**  
OSHA Subpart M 1926.502  
ANSI A10.32-2012,Z359.14-2014



**XR-7W**  
7' web SRL only  
#354-4 (1" opening) steel carabiner  
#Z74 (3/4" opening) locking snap  
Class "A" SRL



**XR-11G**  
11' galvanized steel cable SRL  
#354-4 (1" opening) steel carabiner  
#49 (3/4" opening) locking snap  
Class "A" SRL

**XR-11SS**  
11' stainless steel cable SRL

**XR-11T**  
11' Technora® synthetic rope SRL



**XR-30G**  
30' galvanized steel cable SRL  
#354-4 (1" opening) steel carabiner  
#49 (3/4" opening) locking snap  
Class "B" SRL

**XR-30SS**  
30' stainless steel cable SRL

**XR-30T**  
30' Technora® synthetic rope SRL



**XR-20LEG**  
Leading Edge SRL  
20' galvanized cable only  
#354-4 (1" opening) steel carabiner  
#49 (3/4" opening) locking snap  
Class "B" SRL



**XR-30LEG**  
Leading Edge SRL  
30' galvanized cable only  
#354-4 (1" opening) steel carabiner  
#49 (3/4" opening) locking snap  
Class "B" SRL



**XR-50LEG**  
Leading Edge SRL  
50' galvanized cable only  
#354-4 (1" opening) steel carabiner  
#49 (3/4" opening) locking snap  
Class "B" SRL

**Internal Energy Absorption System**  
Reduces fall arrest forces and minimizes free fall distance should a fall occur.

**Weight Capacity**  
Outlaw series meets:  
ANSI requirement 130-310lbs  
  
OSHA requirement 420lbs or less

**Impact Indicator**  
Locking snap with impact indicator allows for visual inspection of the slightest fall into the unit.



**Swivel Anchor Loop**  
Swivels 360° to limit line twisting for smooth operation.

**Light, Durable Housing**  
High-strength, light weight housing provides excellent durability.

**Short Fall Arrest Activation**  
Unit will stop a fall within inches, reducing fall distances and reducing fall arrest forces to 1,800 lb. or less.

**Leading Edge Shock Absorber**  
Shock pack reduces fall arrest forces. Shock pack free-fall limit 6'. Max elongation distance 48".

**Meets or Exceed Industry Standards**  
OSHA Subpart M 1926.502  
ANSI A10.32-2012,Z359.14-2014

Non-Leading Edge

Leading Edge