



PRODUCT SPECIFICATIONS

22446AW Dual-Leg Shock Absorbing Lanyard

Product Description:

This dual-leg synthetic web lanyard with shock-absorbing pack can be used as a tie-back anchor and limits fall arrest forces to 900 lbs. when tested to OSHA and ANSI standard.

Product Features:

- Dual-leg tie-back lanyard, 100% tie-off
- Internal wear indicating core
- #63 captive eye carabiner on lanyard legs
- Additional lengths available



MATERIAL SPECIFICATIONS	
Webbing	1-3/8" tubular polyester min tensile strength 6,000 lbs.
	1 3/4" tear-away
	1" nylon, minimum tensile strength 6000 lbs.
Hardware	Z74 Locking snap hook 3/4" gate, 100% proof loaded to 3600 lbs.,
	minimum tensile 5000 lbs.
	#63 captive eye carabiner, plated alloy steel
	100% proof loaded to 3600 lbs, minimum tensile 5000 lbs.

MATERIAL SPECIFICATIONS	
Lanyard Class	6' Free Fall
Arrest Force	900 lbs
ANSI User Capacity	130 to 310 lbs
OSHA User Capacity	400 lbs

RELEVANT STANDARDS	
ANSI	Z359.1
OSHA	Meets or exceeds OHSA requirements

Size/Lengths
Standard Length 6' additional lengths available.