

#274 Locking Spreader Snaphook

Product Description:

All FrenchCreek snaps are self-locking and self-closing, and meet the requirements of withstanding a direct force of 3,600 lbs. Each hook can withstand a load of 5,000 lbs.

Product Features:

- 3/4" opening gates
- Proof loaded to 3,600 lbs
- Minimum tensile strength 5,000 lbs




MATERIAL SPECIFICATIONS		
Hardware	Zinc plated alloy steel	
	Gate 3/4" opening, proof loaded up to 3,600 lbs.	
	Minimum tensile strength 5,000 lbs.	
	Gate strength 3,600 lbs.	

MATERIAL SPECIFICATIONS		
OSHA User Capacity	400 lbs. Max	
ANSI User Capacity	130-310 lbs. Max	

RELEVANT STANDARDS		
ANSI	ANSI Z359.12	
OSHA	Meets or exceeds OSHA requirements	

SIZES/LENGTHS



mm (inch)



100 N.13th St. • Franklin PA • 16323 877.228.9327 • 814.437.1808 fcsafety.com **WARNING**: Read, understand and follow all labels and instructions prior to use. Inspect before each use. Remove from service if there is evidence of damage or excessive wear.

REV A **DATE** 9/29/20

PAGE 1