



PRODUCT SPECIFICATIONS

440AZ Shock Absorbing Lanyard

Product Description:

Designed to be easy to use, Frenchcreek lanyards feature many styles, options and lengths. This dual-leg web lanyard with pack style shock absorber limits fall arrest forces to 900 lbs when tested to OSHA and ANSI standards.

Product Features:

- Dual-leg web lanyard with shock absorbing pack (100% tie-off)
- 1" nylon webbing
- Standard length 6', additional lengths available
- Additional snaphook options available

MATERIAL SPECIFICATIONS

Hardware	Z74 Snap hook: 3/4" gate opening, plated cold-formed steel
	100% proof loaded to 3600 lbs min. tensile 5000 lbs
	100% gate loaded to 3600 lbs
Webbing	1" nylon, minimum tensile 6,000 lbs.
	1-3/4" tear-away
	2" black polyester, minimum tensile strength 6,000 lbs.
Thread	White polyester nubond
	Black polyester nubond

MATERIAL SPECIFICATIONS

Lanyard Class	6' free fall
Arrest Force	900 lbs.
ANSI User Capacity	130 to 310 lbs.
OSHA User Capacity	310 lbs.

RELEVANT STANDARDS

ANSI	ANSI Z359.13.2013
OSHA	Meets or exceeds OSHA requirements

SIZES/LENGTHS

Standard length 6' additional sizes may be available.

