



# PRODUCT SPECIFICATIONS

## 442AN Shock Absorbing Lanyard

### Product Description:

Designed to be easy to use, Frenchcreek lanyards feature many styles, options and lengths. This dual-leg web lanyard with pack style shock absorber limits fall arrest forces to 900 lbs when tested to OSHA and ANSI standards.

### Product Features:

Dual-leg web lanyard with shock absorbing pack (100% tie-off)  
1" synthetic webbing  
Standard length 6', additional lengths available  
Additional snaphook options available



MATERIAL SPECIFICATIONS	
<b>Hardware</b>	69N Snap-hook, 1 3/4" gate opening, cold-formed plated steel
	100% proof loaded to 3600 lbs, minimum tensile 5000 lbs,
	100% gate loaded to 3600 lbs
<b>Webbing</b>	Z74 snap hook, 3/4" gate opening, cold plated steel.
	100% proof loaded to 3600 lbs, minimum tensile 5000 lbs,
	gate loaded to 3600 lbs.
<b>Webbing</b>	1" yellow nylon, minimum tensile strength 6000 lbs
	2" black polyester, minimum tensile strength 6000 lbs
<b>Thread</b>	White bonded nylon
	Black bonded nylon

MATERIAL SPECIFICATIONS	
<b>Lanyard Class</b>	6' free fall
<b>Arrest Force</b>	900 lbs.
<b>ANSI User Capacity</b>	130 to 310 lbs.
<b>OSHA User Capacity</b>	400 lbs.

RELEVANT STANDARDS	
<b>ANSI</b>	ANSI Z359.1
<b>OSHA</b>	Meets or exceeds OSHA requirements

SIZES/LENGTHS
Standard length 6' additional sizes may be available.