



PRODUCT SPECIFICATIONS

444A Shock Absorbing Lanyard

Product Description:

Designed to be easy to use, Frenchcreek lanyards feature many styles, options and lengths. This dual-leg web lanyard with pack style shock absorber limits fall arrest forces to 900 lbs when tested to OSHA and ANSI standards.

Product Features:

- Dual-Leg web lanyard with shock absorbing pack (100% tie-off)
- 1" synthetic webbing
- Standard length 6', additional lengths available
- Additional snaphook options available



MATERIAL SPECIFICATIONS	
Hardware	Z136 Snap-hook, 2-1/4" gate opening, cold-formed plated steel
	100% proof loaded to 3600 lbs, minimum tensile 5000 lbs,
	100% gate loaded to 3600 lbs
Webbing	Z74 snap hook, 3/4" gate opening, cold plated steel.
	100% proof loaded to 3600 lbs, minimum tensile 5000 lbs,
	gate loaded to 3600 lbs.
Webbing	1" yellow nylon, minimum tensile strength 6000 lbs
	2" black polyester, minimum tensile strength 6000 lbs
Thread	White bonded nylon
	Black bonded nylon

MATERIAL SPECIFICATIONS	
Lanyard Class	6' free fall
Arrest Force	900 lbs.
ANSI User Capacity	130 to 310 lbs.
OSHA User Capacity	400 lbs.

RELEVANT STANDARDS	
ANSI	ANSI Z359.1
OSHA	Meets or exceeds OSHA requirements

SIZES/LENGTHS
Standard length 6' additional sizes may be available.