



PRODUCT SPECIFICATIONS

446AW Dual-Leg Shock Absorbing Lanyard

Product Description:

This synthetic web lanyard with shock-absorbing pack can be used as a tie-back anchor and limits fall arrest forces to 900 lbs. when tested to OSHA and ANSI standard.

Product Features:

- Dual-leg tie-back lanyard, 100% tie-off
- Internal wear indicating core
- #63 captive eye carabiner on lanyard legs
- Additional lengths available



MATERIAL SPECIFICATIONS	
Hardware	#63 captive eye carabiner, plated alloy steel
	100% proof loaded to 3600 lbs, minimum tensile 5000 lbs,
	100% gate loaded to 3600 lbs
	Z74 snap hook, 3/4" gate opening, cold plated steel.
	100% proof loaded to 3600 lbs, minimum tensile 5000 lbs,
	gate loaded to 3600 lbs.
Webbing	1-3/16" polyester webbing, min tensile strength 6,000 lbs.
Thread	White bonded nylon
	Black bonded nylon

MATERIAL SPECIFICATIONS	
Lanyard Class	6' free fall
Arrest Force	900 lbs.
ANSI User Capacity	130 to 310 lbs.
OSHA User Capacity	400 lbs.

RELEVANT STANDARDS	
ANSI	ANSI Z359.1
OSHA	Meets or exceeds OSHA requirements

SIZES/LENGTHS
Standard length 6' additional sizes may be available.