



# PRODUCT SPECIFICATIONS

## 450ABShock Absorbing Lanyard

### Product Description:

A six foot adjustable web lanyard with a shock absorbing pack and a #Z74 locking snap-hook on each end. Limits fall-arrest forces to 900 lbs. when tested to OSHA and ANSI standards.

### Product Features:

Length is easily adjustable down to half size  
Pack style shock absorber



MATERIAL SPECIFICATIONS	
<b>Webbing</b>	Yellow 1" polyester, tensile strength 9,800 lbs.
	1 3/4" polyester tear-away, ,
	1 3/4" black polyester, minimum tensile strength 6,000 lbs
<b>Thread</b>	Polyester nubond
<b>Hardware</b>	#Z74 snap-hook: 3/4" gate opening, cold-formed plated steel
	100% proof loaded to 3,600 lbs min. tensile strength of 6,000 lbs.
	Adjuster: 1" - 3 bar slide, stamped plated steel, min tensile 4,000 lbs

MATERIAL SPECIFICATIONS	
<b>Lanyard Class</b>	6' free fall
<b>Arrest Force</b>	900 lbs.
<b>ANSI User Capacity</b>	130 to 310 lbs.
<b>OSHA User Capacity</b>	400 lbs.

RELEVANT STANDARDS	
<b>ANSI</b>	ANSI Z359.1
<b>OSHA</b>	Meets or exceeds OSHA requirements

SIZES/LENGTHS
Standard length 6' additional sizes available.