



# PRODUCT SPECIFICATIONS

## 450AS Shock Absorbing Lanyard

### Product Description:

This lanyard with shock absorbing pack limits fall arrest forces to 900lbs when tested to OSHA and ANSI standards.

### Product Features:

- Stretches to minimize tripping hazards
- Standard length of 6', relaxes to approximately 4.5' when not stretched
- Additional snaphook options available
- 1 3/16" Synthetic tubular webbing



### MATERIAL SPECIFICATIONS

<b>Webbing</b>	1-3/16" polyester tubular webbing minimum tensile strength 6000 lbs.
	1-3/4" black polyester, minimum tensile strength 6,000 lbs
	1-3/4" tear-away
<b>Hardware</b>	#Z74 snap-hooks: 3/4" gate opening, zinc plated steel
	100% proof loaded to 3,600 lbs min. tensile strength of 5,000 lbs.
<b>Thread</b>	Polyester nubond

### MATERIAL SPECIFICATIONS

<b>Lanyard Class</b>	6' free fall
<b>Arrest Force</b>	900 lbs.
<b>ANSI User Capacity</b>	130 to 310 lbs.
<b>OSHA User Capacity</b>	400 lbs.

### RELEVANT STANDARDS

<b>ANSI</b>	ANSI Z359.13-2013
<b>OSHA</b>	Meets or exceeds OSHA requirements

### SIZES/LENGTHS

Standard length 6' additional sizes available  
Weight 2.30 lbs.