



# PRODUCT SPECIFICATIONS

## 450B Positioning Lanyard

### Product Description:

Six foot adjustable length non-shock absorbing lanyard, for positioning or restraint only. Must be paired with approved shock absorbing device for fall-arrest.

### Product Features:

- Standard length of six feet
- Adjustable length
- Additional snaphook options available

### MATERIAL SPECIFICATIONS

<b>Hardware</b>	#Z74 snap hooks, 3/4" gate opening, plated alloy steel
	100% proof loaded to 3,600 lbs, minimum tensile 5,000 lbs
	Gate proof loaded to 3,600 lbs
<b>Adjuster</b>	N-452L, 1- 3" bar slide, zinc plated steel, min tensile 5,000 lbs
<b>Webbing</b>	Yellow 1" wide polyester, minimum tensile strength 9,800 lbs
<b>Thread</b>	Polyester nubond

### MATERIAL SPECIFICATIONS

<b>Lanyard Class</b>	3' < Positioning
<b>ANSI User Capacity</b>	130 to 310 lbs.
<b>OSHA User Capacity</b>	400 lbs.

### RELEVANT STANDARDS

<b>ANSI</b>	ANSI Z359.1-2007
<b>OSHA</b>	Meets or exceeds OSHA requirements

### SIZES/LENGTHS

Standard length 6' additional sizes available  
Weight 2 lbs.

