



PRODUCT SPECIFICATIONS

454AS Shock Absorbing Lanyard

Product Description:

This lanyard with shock absorbing pack limits fall arrest forces to 900lbs when tested to OSHA and ANSI standards.

Product Features:

- Stretches to minimize tripping hazards
- Standard length of 6'
- Additional snaphook options available
- 1 3/16" Synthetic tubular webbing

MATERIAL SPECIFICATIONS

Hardware	#Z74 snap hook, 3/4" gate opening, cold-formed plated steel
	100% proof loaded to 3600 lbs, minimum tensile 5000 lbs
	Gate proof loaded to 3600 lbs
	Z136 Locking snap hook 2 1/4" gate opening
Webbing	1 3/16" Polyester tubular webbing minimum tensile strength 6000 lbs.
	1 3/4" tear-away
	1 3/4" polyester, minimum tensile strength 6000 lbs.



MATERIAL SPECIFICATIONS

Lanyard Class	6 ft. free fall
Arrest Force	900 lbs.
ANSI User Capacity	130 to 310 lbs.
OSHA User Capacity	400 lbs.

RELEVANT STANDARDS

ANSI	ANSI Z359.1
OSHA	Meets or exceeds OSHA requirements

SIZES/LENGTHS

Standard length 6' additional sizes available.