



# PRODUCT SPECIFICATIONS

## 456AW Dual-Leg Shock Absorbing Lanyard

### Product Description:

This synthetic web lanyard with shock-absorbing pack can be used as a tie-back anchor and limits fall arrest forces to 900 lbs. when tested to OSHA and ANSI standard.

### Product Features:

- Tie-back lanyard
- Internal wear indicating core
- #63 captive eye carabiner on lanyard legs
- Additional lengths available



MATERIAL SPECIFICATIONS	
<b>Webbing</b>	1-3/8" tubular polyester min tensile strength 6,000 lbs.
	1 3/4" tear-away
	1" nylon, minimum tensile strength 6000 lbs.
<b>Hardware</b>	#Z74 snap hook 3/4" gate opening, cold formed plated steel
	100% proof loaded to 3600 lbs, min. tensile 5000 lbs
	#63 captive eye carabiner, plated alloy steel
	100% proof loaded to 3600 lbs, minimum tensile 5000 lbs.

MATERIAL SPECIFICATIONS	
<b>Lanyard Class</b>	6' free fall
<b>Arrest Force</b>	900 lbs.
<b>ANSI User Capacity</b>	130 to 310 lbs.
<b>OSHA User Capacity</b>	310 lbs.

RELEVANT STANDARDS	
<b>ANSI</b>	ANSI Z359.1
<b>OSHA</b>	Meets or exceeds OSHA requirements

SIZES/LENGTHS	
Standard length 6' additional sizes may be available.	