



PRODUCT SPECIFICATIONS

459 Self-Retracting Lifeline

Product Description:

The design of the 459 Self-Retracting Lifeline is simple, yet effective. With 8' of working length the 459 SRL can economically replace simple lanyards.

Product Features:

- Lightweight Synthetic Housing
- Centrifugal Breaking Mechanism
- Short fall arrest "Class 1" SRL
- 3/4" gate opening self-locking snaphook



MATERIAL SPECIFICATIONS	
Webbing	8' length, 2" wide polyester, min tensile 6,000 lbs
Wear Pad	1-3/16" polyester tubular web
Hardware	Carabiner: (1" opening) alloy steel triple lock carabiner 3,600 lb. gate Minimum tensile strength 5,000 lbs. Snaps: (3/4" opening) alloy steel locking snaphook 3,600 lb. gate Minimum tensile strength 5,000 lbs.
Housing	Lightweight Synthetic Housing

MATERIAL SPECIFICATIONS	
Arresting Force	Average arresting force 900 lbs., Maximum arresting force 1,800 lbs.
Max Fall Distance	48"
Capacity	400 lbs. OSHA

RELEVANT STANDARDS	
ANSI	ANSI Z359.14 2021 Class 1
OSHA	Meets or exceeds OSHA requirements

SIZES/LENGTHS
8' length