## 459 Self-Retracting Lifeline

## **Product Description:**

The design of the 459 Self-Retracting Lifeline is simple, yet effective. With 8' of working length the 459 SRL can economically replace simple lanyards.

## **Product Features:**

- Lightweight Synthetic Housing
- · Centrifugal Breaking Mechanism
- · Short fall arrest "Class A" SRL
- 3/4" gate opening self-locking snaphook

MATERIAL SPECIFICATIONS		
Webbing	8' length, 2" wide polyester, min tensile 6,000 lbs	
Wear Pad	1-3/16" polyester tubular web	
Hardware	Carabiner: (1" opening) alloy steel triple lock carabiner 3,600 lb. gate	
	Minimum tensile strength 5,000 lbs.	
	Snaps: (3/4" opening) alloy steel locking snaphook 3,600 lb. gate	
	Minimum tensile strength 5,000 lbs.	
Housing	Lightweight Synthetic Housing	

MATERIAL SPECIFICATIONS			
Arresting Force	Average arresting force 900 lbs., Maximum arresting force 1,800 lbs.		
Max Fall Distance	48"		
Capacity	400 lbs. OSHA		

RELEVANT STANDARDS		
ANSI	ANSI Z359.14	
OSHA	Meets or exceeds OSHA requirements	

SIZES/LENGTHS		
8' length		



