

460A Shock Absorbing Lanyard

Product Description:

This synthetic webbing lanyard with shock absorbing core limits fall arrest forces to 900 lbs. when tested to OSHA and ANSI standards.

Product Features:

- 1-3/16" tubular synthetic webbing
- Standard length 6', additional lengths available
- Additional snaphook options available

MATERIAL SPECIFICATIONS		
Webbing	Yellow 1-3/16" tubular synthetic webbing	
Thread	Polyester Nubod	
Hardware	#Z74 snap-hook: 3/4" gate opening, cold-formed plated steel	
	100% proof loaded to 3,600 lbs. min tensile strength of 5,000 lbs	



MATERIAL SPECIFICATIONS		
Lanyard Class	6' Free Fall	
Arrest Force	900 lbs	
ANSI User Capacity	130 to 310 lbs	
OSHA User Capacity	310 lbs	

RELEVANT STANDARDS		
ANSI	Z359.1	
OSHA	Meets or exceeds OHSA requirements	

Size/Lenghts

Standard Length 6' additional lengths available.



100 N.13th St. • Franklin PA • 16323 877.228.9327 • 814.437.1808 fcsafety.com **WARNING**: Read, understand and follow all labels and instructions prior to use. Inspect before each use. Remove from service if there is evidence of damage or excessive wear.

REV A **DATE** 06/21/2023 **PAGE** 1