

552 Full Body Harness

Product Description:

In many situations, a specialty harness may be necessary for ensured safety. These harnesses meet the specific requirements and help workers in these fields work safely.

Product Features:

- 6-point adjustable harness
- · Miners harness with lamp and battery straps
- Dual lanyard retainer rings
- 152" of reflective material
- Tongue buckle/grommet leg straps
- · Lightweight, high strength synthetic webbing

| MATERIAL SPECIFICATIONS | | | |
|-------------------------|---|--|--|
| Webbing | 1-3/4" polyester webbing min tensile strength 6,000 lbs | | |
| | | | |
| Hardware | D-ring: plated alloy steel proof loaded to 3,600 lbs. | | |
| | Min tensile strength 5,000 lbs. | | |
| | Tongue Buckles: plated alloy steel, min tensile strength 4,000 lbs. | | |
| | Friction Buckles: plated alloy steel, min tensile strength 4,000 lbs. | | |
| | Grommets: #2 Brass spur washer and grommet | | |
| | | | |
| Padding | Comfort mesh shoulder pads | | |
| | | | |

| MATERIAL SPECIFICATIONS | | |
|-------------------------|----------------|--|
| ANSI User Capacity | 130 to 310 lbs | |
| OSHA User Capacity | 400 lbs | |
| | | |
| | | |

| RELEVANT STANDARDS | | | |
|--------------------|--|--|--|
| ANSI | ANSI Z359.1 | | |
| OSHA | Meets or exceeds all OSHA requirements | | |
| | | | |
| | | | |

| SIZES/LENGTHS | | | |
|---------------------------|--|--|--|
| XS, S, M, L, XL, 2XL, 3XL | | | |
| | | | |

