



# PRODUCT SPECIFICATIONS

## 631B-HOT Full Body Harness

### Product Description

FrenchCreek manufactures these harnesses out of high strength Kevlar® webbing that meets the heat and flame resistance requirements that occur in harsh environments.

### Product Features

- 3 point adjustment (chest and leg straps)
- Sliding back dorsal D-ring
- Heat & Flame resistant Kevlar® webbing
- Hip-positioning D-rings
- Two universal sizes



### MATERIAL SPECIFICATIONS

|                 |   |
|-----------------|---|
| <b>Webbing</b>  | 1-3/4" Kevlar® webbing, minimum tensile strength 7,000 lbs.   |
| <b>Hardware</b> | Mating Buckles: plated alloy steel, min tensile strength 4,000 lbs.<br>D-rings: plated alloy steel, 100% proof loaded to 3,600 lbs.<br>Minimum tensile strength of 5,000 lbs. |
| <b>Thread</b>   | Kevlar® thread  |
|                 |   |
|                 |   |
|                 |   |
|                 |   |

### PERFORMANCE SPECIFICATIONS

|                           |                |
|---------------------------|----------------|
| <b>ANSI User Capacity</b> | 130 to 310 lbs |
| <b>OSHA User Capacity</b> | 400 lbs        |
|                           |                |
|                           |                |

### RELEVANT STANDARDS

|             |  |
|-------------|--|
| <b>ANSI</b> | ANSI Z359.1                            |
| <b>ANSI</b> | Meets or exceeds all OSHA requirements |
|             |  |
|             |  |

### SIZES/LENGTHS

|  |
|--|
| <b>Two universal sizes: S-M and M-XL</b> |
|--|