



PRODUCT SPECIFICATIONS

651B Full Body Harness

Product Description:

In many situations, a specialty harness may be necessary for ensured safety. These harnesses meet the specific industry requirements and help workers in these fields work safely.

Product Features:

- 3 point adjustable harnesses
- Built in life jacket Type 3 PFD
- Mating buckle leg straps
- Sliding back D-ring for lanyard attachment



| MATERIAL SPECIFICATIONS | |
|-------------------------|--|
| Webbing | 1-3/4" polyester webbing, minimum tensile strength 6,000 lbs. |
| Hardware | D-ring: Plated alloy steel, 100% proof loaded to 3,600 lbs. min tensile strength 5,000 lbs. |
| | Mating Buckles: plated alloy steel minimum tensile strength 4,000 lbs. |
| Vest | 10 flotation panels for a flexible, contoured fit |
| | Nylon outer shell with marine mesh inner lining |
| | 62 sq. in. of 3M Scotchlite reflective material SOLAS-grad 6755 panels |
| | Minimum 15-1/2 lb. buoyancy |
| | USCG approved Type III |
| | Chest pocket and rust proof zipper and body belt |

| MATERIAL SPECIFICATIONS | |
|---------------------------|--------------|
| ANSI Capacity | 130-310 lbs. |
| OSHA User Capacity | 400 lbs. |
| | |
| | |

| RELEVANT STANDARDS | |
|--------------------|--|
| ANSI | ANSI Z359.1 |
| OSHA | Meets or exceeds all OSHA requirements |
| | |
| | |

| SIZES/LENGTHS |
|---------------|
| S-M, M-XL |

