



PRODUCT SPECIFICATIONS

650-U Full Body Harness

Product Description:

The 600 series harnesses incorporate a lightweight design that will give your workers the freedom of movement when working from height.

Product Features:

- Adjustable shoulder, chest and leg straps
- Sub-pelvic strap
- Break-away lanyard retainers
- Sliding Back D-ring
- Lightweight, synthetic webbing



MATERIAL SPECIFICATIONS

Webbing	1-3/4" polyester, min tensile strength 6,500 lbs.
Hardware	D-rings: plated alloy steel, powder coated, proof loaded to 3,600 lbs., min. tensile strength 4,000 lbs.
	Bayonet buckles: Plated alloy steel, min tensile 4,000 lbs.
	Friction buckles: Plated alloy steel, min tensile 4,000 lbs.
	Tongue buckles: Plated alloy steel, min tensile 4,000 lbs.
	Grommets: #2 Brass spur washer and grommet
Thread	Black nubond

MATERIAL SPECIFICATIONS

OSHA User Capacity	130 to 310 lbs.
ANSI User Capacity	400 lbs.

RELEVANT STANDARDS

ANSI	ANSI Z359.11-2014
OSHA	Meets or exceeds all OSHA requirements

SIZES/LENGTHS

Universal Size
