

950B Full Body Harness

Product Description:

The 900 series can be used in a multitude of applications. The harness is donned by a step-thru procedure that is quick and easy.

Product Features:

- Front cross-over style
- 4 point adjustment
- Adjustable shoulder and leg straps
- Hip-positioning D-rings
- · Chest D-rings for positioning, suspension and rescue
- Lightweight, high strength synthetic webbing

MATERIAL SPECIFICATIONS		
Webbing	1-3/4" polyester webbing min tensile strength 6,000 lbs	
Hardware	D-ring: plated alloy steel proof loaded to 3,600 lbs.	
	Min tensile strength 5,000 lbs.	
	Grommets: #2 Brass spur washer and grommet	
	Friction Buckles: plated alloy steel, min tensile strength 4,000 lbs.	
	Tongue Buckles: plated alloy steel, min tensile strength 4,000 lbs.	

Hardware	D-ring: plated alloy steel proof loaded to 3,600 lbs.	
	Min tensile strength 5,000 lbs.	
	Grommets: #2 Brass spur washer and grommet	
	Friction Buckles: plated alloy steel, min tensile strength 4,000 lbs.	
	Tongue Buckles: plated alloy steel, min tensile strength 4,000 lbs.	

MATERIAL SPECIFICATIONS		
ANSI User Capacity	130 to 310 lbs	
OSHA User Capacity	400 lbs	

RELEVANT STANDARDS		
ANSI	ANSI Z359.11-2021	
OSHA	Meets or exceeds all OSHA requirements	

SIZES/LENGTHS				
XS, S, M, L, XL, 2XL, 3XL				

