AF390AKDLZ Kevlar Shock Absorbing Lanyard

Product Description:

FrenchCreek's Arc Flash lanyards offer fall protection, and protection against electrical arc-flash and arc-blast exposure. These lanyards are made from heat & flame resistant Kevlar webbing.

Product Features:

- Kevlar webbing
- · Harness choke loop
- Dual-leg (100% tie-off)
- Z74 (3/4" opening) locking snaphook
- Flame resistant shock & label cover
- · Additonal snaphook options available

MATERIAL SPECIFICATIONS		
Webbing	1-3/4" Kevlar webbing, minimum tensile strength 7,000 lbs.	
Hardware	Z74 Snaphook: 3/4" gate opening, plated cold-formed steel	
	100% proof loaded to 3,600 lbs., minimum tensile 5,000 lbs.	
	100% gate loaded to 3,600 lbs.	
Thread	Kevlar	



MATERIAL SPECIFICATIONS			
ANSI User Capacity	130 to 310 lbs		
OSHA User Capacity	400 lbs		
Lanyard Class	6' Free Fall		
Arrest Force	900 lbs		

RELEVANT STANDARDS		
ANSI	ANSI Z359.1	
OSHA	Meets or exceeds all OSHA requirements	
ASTM	F887-13	

SIZES/LENGTHS
6' standard length, additional lengths available

