



PRODUCT SPECIFICATIONS

AF390AKZ Kevlar Shock Absorbing Lanyard

Product Description:

FrenchCreek's Arc Flash lanyards offer fall protection, and protection against electrical arc-flash and arc-blast exposure. These lanyards are made from heat & flame resistant Kevlar webbing.

Product Features:

- Kevlar webbing
- Harness choke loop
- Z74 (3/4" opening) locking snaphook
- Flame resistant shock & label cover
- Additional snaphook options available



MATERIAL SPECIFICATIONS	
Webbing	1-3/4" Kevlar webbing, minimum tensile strength 7,000 lbs.
Hardware	Z74 Snaphook: 3/4" gate opening, plated cold-formed steel
	100% proof loaded to 3,600 lbs., minimum tensile 5,000 lbs.
	100% gate loaded to 3,600 lbs.
Thread	Kevlar

MATERIAL SPECIFICATIONS	
ANSI User Capacity	130 to 310 lbs
OSHA User Capacity	400 lbs
Lanyard Class	6' Free Fall
Arrest Force	900 lbs

RELEVANT STANDARDS	
ANSI	ANSI Z359.1
OSHA	Meets or exceeds all OSHA requirements
ASTM	F887-13

SIZES/LENGTHS
6' standard length, additional lengths available