



# PRODUCT SPECIFICATIONS

## M2RG-0Z Rogue Dual-Leg SRL

### Product Description:

The Rogue features a Dual-Leg configuration perfect for 100% tie-off allowing a worker to move freely and transition from anchor point to anchor point safely.

### Product Features:

- 8' dual-leg web SRL
- 2-1/2" locking aluminum rebar snaphook on legs
- Class "A" SRL
- Attaches to harness back



MATERIAL SPECIFICATIONS	
<b>Webbing</b>	1" X 0.05" Dyneema & Polyester Webbing
<b>Housing</b>	UV Resistant Nylon
	Drum: Nylon
	Pawls, Fasteners and Springs: Stainless Steel
<b>Hardware</b>	Carabiner: (1" opening) alloy steel triple lock carabiner 3,600 lb. gate
	Minimum tensile strength 5,000 lbs.
	Snaps: (2-1/2" opening) aluminum locking rebar snap 3,600 lb. gate
	Minimum tensile strength 5,000 lbs.

MATERIAL SPECIFICATIONS	
<b>Arresting Force</b>	Average arresting force 900 lbs., Maximum arresting force 1,800 lbs.
<b>Maximum fall distance</b>	24 inches
<b>OSHA User Capacity</b>	400 lbs
<b>ANSI User Capacity</b>	130 to 310 lbs

RELEVANT STANDARDS	
<b>ANSI</b>	ANSI Z359.14 Class A
<b>OSHA</b>	Meets or exceeds all OSHA requirements

SIZES/LENGTHS
XS, S-M, L-XL, 2XL, 3XL