



PRODUCT SPECIFICATIONS

M2RG-4AZ Rogue Dual-Leg SRL

Product Description:

The Rogue features a Dual-Leg configuration perfect for 100% tie-off allowing a worker to move freely and transition from anchor point to anchor point safely.

Product Features:

- 8' dual-leg web SRL
- 2-1/2" locking aluminum rebar snaphook on legs
- Class "1" SRL
- Attaches to harness back



MATERIAL SPECIFICATIONS

Webbing	1" X 0.05" Dyneema & Polyester Webbing
Housing	UV Resistant Nylon
	Drum: Nylon
	Pawls, Fasteners and Springs: Stainless Steel
Hardware	Carabiner: (1" opening) alloy steel triple lock carabiner 3,600 lb. gate
	Minimum tensile strength 5,000 lbs.
	Snap: (2-1/2" opening) aluminum locking rebar snap 3,600 lb. gate
	Minimum tensile strength 5,000 lbs.

MATERIAL SPECIFICATIONS

Arresting Force	Average arresting force 900 lbs., Maximum arresting force 1,800 lbs.
Maximum fall distance	24 inches
OSHA User Capacity	400 lbs
ANSI User Capacity	130 to 310 lbs

RELEVANT STANDARDS

ANSI	ANSI Z359.14 2021 Class 1
OSHA	Meets or exceeds all OSHA requirements

SIZES/LENGTHS

XS, S-M, L-XL, 2XL, 3XL