

M2RG-4Z Rogue Self-Retracting Lifeline

Product Description:

The Rogue features a Dual-Leg configuration perfect for 100% tie-off allowing a worker to move freely and transition from anchor point to anchor point safely.

Product Features:

- 8' dual-leg web SRL
- 2-1/2" locking rebar snaps on legs
- · Class "A" SRL
- Attaches to harness back

MATERIAL SPECIFICATIONS		
Webbing	1" X 0.05" Dyneema & Polyester Webbing	
Housing	UV Resistant Nylon	
	Drum: Nylon	
	Pawls, Fasteners and Springs: Stainless Steel	
Hardware	Carabiner: (1" opening) alloy steel triple lock carabiner 3,600 lb. gate	
	Minimum tensile strength 5,000 lbs.	
	Snaps: (2-1/2" opening) alloy steel locking rebar snap 3,600 lb. gate	
	Minimum tensile strength 5,000 lbs.	

MATERIAL SPECIFICATIONS				
Arresting Force	Average arresting force 900 lbs., Maximum arresting force 1,800 lbs.			
Maximum fall distance	24 inches			
OSHA User Capacity	400 lbs			
ANSI User Capacity	130 to 310 lbs			

RELEVANT STANDARDS			
ANSI	ANSI Z359.14 Class A		
OSHA	Meets or exceeds all OSHA requirements		

SIZES/LENGTHS				
8' length				

