

OUTLAW

Self-Retracting Lifelines

Internal Energy Absorption System
Reduces fall arrest forces and minimizes free fall distance should a fall occur.

Weight Capacity
Outlaw series meets:
ANSI requirement 130-310 lbs.

OSHA requirement 400 lbs.

Impact Indicator
Locking snap with impact indicator allows for visual inspection of the slightest fall into the unit

Class
1
Anchor at or above dorsal D-ring

Meets or Exceed Industry Standards
OSHA Subpart M 1926.502, ANSI Z359.14-2021

Swivel Anchor Loop
Swivels 360° to limit line twisting for smooth operation

Light, Durable Housing
High-strength, light weight housing provides excellent durability

Short Fall Arrest Activation
Unit will stop a fall within inches, reducing fall distances and reducing fall arrest forces to 1,800 lbs., or less

Lifeline Constituents
Choose the cable type to meet the specific needs of your job requirement:
Galvanized Steel
Stainless Steel
Technora® synthetic rope

Outlaw Series Self-Retracting Lifeline (XR Series)

The Outlaw Series SRL's provide durability and confidence expected by professionals. With 7, 11, and 30 feet of working capacity and short fall arrest capability, the Outlaw will never let you down.

XR-7W



XR-7W
7' web SRL
#354-4 (1" opening) steel carabiner
#274 (3/4" opening) locking snap
Class "1" SRL

XR-11G



XR-11G
11' galvanized steel cable SRL
#354-4 (1" opening) steel carabiner
RL-28 (3/4" opening) locking snap
Class "1" SRL

XR-11S
11' stainless steel cable SRL

XR-11T
11' Technora® synthetic rope SRL

XR-30G



XR-30G
30' galvanized steel cable SRL
#354-4 (1" opening) steel carabiner
RL-28 (3/4" opening) locking snap
Class "1" SRL

XR-30S
30' stainless steel cable SRL

XR-30T
30' Technora® synthetic rope SRL

OUTLAW

Leading Edge Self-Retracting Lifelines

Internal Energy Absorption System
Reduces fall arrest forces and minimizes free fall distance should a fall occur.

Weight Capacity
Outlaw series meets:
ANSI requirement 130-310 lbs.

OSHA requirement 400 lbs.

Impact Indicator
Locking snap with impact indicator allows for visual inspection of the slightest fall into the unit.

Class
2
Anchor above or below dorsal D-ring

Meets or Exceed Industry Standards
OSHA Subpart M 1926.502, ANSI Z359.14-2021

Swivel Anchor Loop
Swivels 360° to limit line twisting for smooth operation.

Light, Durable Housing
High-strength, light weight housing provides excellent durability.

Leading Edge Shock Pack
Shock pack reduces fall arrest forces. Shock pack free-fall limit 6'. Max elongation distance 48". Reduces fall arrest forces to 1,800 lbs., or less

Outlaw Series-Leading Edge Self-Retracting Lifeline (XR Series)

Enter the next level in fall protection with the Outlaw LE SRL, and give your workers confidence while working on the edge.

- Internal energy absorption system
- External shock absorbing pack



XR-50LEG
50' galvanized cable Leading Edge SRL
#354-4 (1" opening) steel carabiner
RL-28 (3/4" opening) locking snap
Class "2" SRL



XR-30LEG
30' galvanized cable Leading Edge SRL
#354-4 (1" opening) steel carabiner
RL-28 (3/4" opening) locking snap
Class "2" SRL



XR-20LEG
20' galvanized cable Leading Edge SRL
#354-4 (1" opening) steel carabiner
RL-28 (3/4" opening) locking snap
Class "2" SRL