



PRODUCT SPECIFICATIONS

RL25AGZ Self-Retracting Lifeline

Product Description:

The RL Series features extreme durability with high mobility. These units offer an extended range of movement with zero slack to eliminate tripping hazards.

Product Features:

- Aluminum cast housing
- Dual internal inertia braking system
- Galvanized wire rope lifeline
- 25' length of working length, additional lengths available
- Class 1 SRL



MATERIAL SPECIFICATIONS	
Lifeline	25' synthetic webbing
Housing	Aluminum cast housing, powdered coated
	Fasteners and Springs: Stainless Steel
	Brake Pawls: Bronze
Hardware	Snaps: (3/4" opening) alloy steel locking snaphook 3,600 lb. gate
	5,000 min tensile strength
	Carabiner: (1" opening) alloy steel triple lock carabiner 3,600 lb. gate
	5,000 min tensile strength
	Energy Absorber: Polyester

MATERIAL SPECIFICATIONS	
Arresting Force	Average arresting force 900 lbs., Maximum arresting force 1,800 lbs.
Maximum Arrest distance	54 inches
OSHA Capacity	400 lbs.
ANSI Capacity	130-310 lbs.

RELEVANT STANDARDS	
ANSI	ANSI Z359.14-2021 "Class 1"
OSHA	OSHA 1926.502, 1910.66

SIZES/LENGTHS
25' length, additional lengths available