

PRODUCT SPECIFICATIONS

XR-11G Outlaw Self-Retracting Lifeline

Product Description

The Outlaw Series SRL's provide durability and confidence expected by professionals. All units feature lightweight housings, and short fall arrest capabilities

Product Features

- 11' steel cable
- Class "1" SRL
- 3/4" opening swivel snaphook
- 1" opening steel carabiner
- Also available in stainless steel cable or technora synthetic rope.

MATERIAL SPECIFICATIONS				
Lifeine Constituent	11' galvanized steel cable			
Housing/Hardware	Thermo-plastic and aluminum			
	Drum: Aluminum Alloy			
	Ratchet Center & Brake Pawls: Brass			
	Springs & Fastners: Stainless Steel			
Carabiner	Plated alloy steel, 3,600 lb. gate, Min tensile strength 5,000 lbs.			
Snaphook	Plated alloy steel, 3,600 lb. gate, Min tensile strength 5,000 lbs.			

PERFORMANCE SPECIFICATIONS			
Arresting Force	Average arresting force 1350 lbs., Maximum arresting force 1,800 lbs.		
Maximum Arrest distance	24 inches		
OSHA Capacity	420 lbs.		
ANSI Capacity	130-310 lbs.		

	RELEVANT STANDARDS
ANSI	ANSI Z359.14-2021, "Class 1" SRL
OSHA	Meets OSHA requiremenets

	SIZES/LENGTHS	
11' length		



