



PRODUCT SPECIFICATIONS

XR-20LEG Outlaw Leading Edge Self-Retracting Lifeline

Product Description:

The Outlaw Series SRL's provide durability and confidence expected by professionals. All units feature lightweight housings, and short fall arrest capabilities. Leading edge models feature an energy absorption pack to reduce fall arrest forces.

Product Features:

- 20' steel cable
- Class "2" SRL
- 3/4" opening swivel snaphook
- 1" opening steel carabiner
- Energy absorption pack



MATERIAL SPECIFICATIONS	
Lifeline	20' galvanized steel cable
Housing/ Hardware	Thermo-plastic and aluminum
	Drum: Aluminum Alloy
	Ratchet Center & Brake Pawls: Brass
	Springs & Fasteners: Stainless Steel
Energy Absorber	Polyester
Carabiner	Plated alloy steel, 3,600 lb. gate, Min tensile strength 5,000 lbs.
Snaphook	Plated alloy steel, 3,600 lb. gate, Min tensile strength 5,000 lbs.

MATERIAL SPECIFICATIONS	
Arresting Force	Average arresting force 900 lbs., Maximum arresting force 1,800 lbs.
Maximum Arrest distance	54 inches
OSHA Capacity	420 lbs.
ANSI Capacity	130-310 lbs.

RELEVANT STANDARDS	
ANSI	ANSI Z359.14-2021, 'Class 2" SRL
OSHA	Meets OSHA requiremenets

SIZES/LENGTHS
20' length