



# PRODUCT SPECIFICATIONS

## XR-20LEG Outlaw Leading Edge Self-Retracting Lifeline

### Product Description:

The Outlaw Series SRL's provide durability and confidence expected by professionals. All units feature lightweight housings, and short fall arrest capabilities. Leading edge models feature an energy absorption pack to reduce fall arrest forces.

### Product Features:

- 20' steel cable
- Class "2" SRL
- 3/4" opening swivel snaphook
- 1" opening steel carabiner
- Energy absorption pack

### MATERIAL SPECIFICATIONS

|                   |                                                                                                |
|-------------------|------------------------------------------------------------------------------------------------|
| Lifeine           | 20' galvanized steel cable                                                                     |
| Housing/ Hardware | Thermo-plastic and aluminum                                                                    |
|                   | Drum: Aluminum Alloy, Main Shaft: Stainless Steel                                              |
|                   | Ratchet Center & Brake Pawls: Brass                                                            |
|                   | Springs & Fastners: Stainless steel, Motor Spring: Carbon Steel                                |
| Energy Absorber   | Polyester, 1-3/4" tear away                                                                    |
| Carabiner         | #354-4, 1" Gate Opening, Plated Alloy Steel<br>3,600 lb. gate, Min tensile strength 5,000 lbs. |
| Snaphook          | 3/4" Gate opening Aluminum Swivel Snap with<br>Impact Indicator                                |
|                   | 3,600 lb Gate, Min Tensile Strength 5,000 lbs                                                  |

### MATERIAL SPECIFICATIONS

|                         |                                                                           |
|-------------------------|---------------------------------------------------------------------------|
| Arresting Force         | Average arresting force 1,350 lbs.,<br>Maximum arresting force 1,800 lbs. |
| Maximum Arrest distance | 42 inches                                                                 |
| OSHA Capacity           | 400 lbs.                                                                  |
| ANSI Capacity           | 130-310 lbs.                                                              |

### RELEVANT STANDARDS

|      |                                  |
|------|----------------------------------|
| ANSI | ANSI Z359.14-2021, 'Class 2" SRL |
| OSHA | Meets OSHA requiremenets         |
|      |                                  |
|      |                                  |

### SIZES/LENGTHS

20' length  
Weight: 10 lbs

