XR-30LEG Outlaw Leading Edge Self-Retracting Lifeline

Product Description:

The Outlaw Series SRL's provide durability and confidence expected by professionals. All units feature lightweight housings, and short fall arrest capabilities. Leading edge models feature an energy absorption pack to reduce fall arrest forces.

Product Features:

- 30' steel cable
- · Class "B" SRL
- 3/4" opening swivel snaphook
- 1" opening steel carabiner
- Energy absorption pack

MATERIAL SPECIFICATIONS		
Lifeine	30' galvanized steel cable	
Housing/ Hardware	Thermo-plastic and aluminum	
	Drum: Aluminum Alloy	
	Ratchet Center & Brake Pawls: Brass	
	Springs & Fastners: Stainless Steel	
Energy Absorber	Polyester	
Carabiner	Plated alloy steel, 3,600 lb. gate, Min tensile strength 5,000 lbs.	
Snaphook	Plated alloy steel, 3,600 lb. gate, Min tensile strength 5,000 lbs.	

MATERIAL SPECIFICATIONS			
Arresting Force	Average arresting force 900 lbs., Maximum arresting force 1,800 lbs.		
Maximum Arrest distance	54 inches		
OSHA Capacity	420 lbs.		
ANSI Capacity	130-310 lbs.		

RELEVANT STANDARDS		
ANSI	ANSI Z359.14, A10.32 "Class B" SRL	
OSHA	Meets OSHA requiremenets	

SIZES/LENGTHS
30' length

