## **850B-TS Full Body Harness**

## **Product Description**

The 800 series harnesses are extremely durable and comfortable. With a range that is extensive with a suitable model for every user the 800 series is a long time favorite in many different job applications.

## **Product Features**

- 6 point adjustment
- Waist D-ring for vertical climbing systems
- Tongue buckle/grommet leg straps
- Hip Positioning D-rings
- Break-away lanyard retainers
- Impact Indicators

MATERIAL SPECIFICATIONS	
Webbing	1-3/4" polyester, minimum tensile strength 6,000 lbs.
Hardware	Grommets: brass with anti-rotational spur washers
	Tongue buckles: plated alloy steel, min tensile strength 4,000 lbs.
	Mating buckles: plated alloy steel, min tensile strength 4,000 lbs.
	Friction buckles: plated alloy steel, min tensile strength 4,000 lbs.
	D-rings: plated alloy steel, proof loaded 3600 lbs, min tensile 5000 lbs.
Padding	Cool Max foam waist pad

PERFORMANCE SPECIFICATIONS		
ANSI User Capacity	130-310 lbs. Max	
OSHA User Capacity	400 lbs. Max	

	RELEVANT STANDARDS
ANSI	Z359.11-2021
OSHA	Meets or exceeds all OSHA requirements

## SIZES/LENGTHS

XS, S, M, L, XL, 2XL, 3XL



FrenchCreek\_ FALL SAFETY REV: A DATE: 11/03/20 PAGE: 1

100 N 13th St. • Franklin PA • 16323 877.228.9327 • 814-437-1808 frenchcreekproduction.com

WARNING: Read, understand and follow all labels and instructions prior to use, Inspect before each use. Remove from service if there is evidence of damage or excessive wear