



# PRODUCT SPECIFICATIONS

## 450 Positioning/Restraint Lanyard

### Product Description

FrenchCreek positioning lanyards are not to be used as a fall arrest device. They are for restraint only, to keep workers at a safe distance. These are to be used in conjunction with a full body harness, and should be used with a back-up fall arrest device.

### Product Features

- 1" nylon webbing
- Standard length 6', additional lengths available
- Additional snaphook options available
- Restraint & Positioning ONLY



### MATERIAL SPECIFICATIONS

<b>Hardware</b>	Z74 snaphook: 3/4" gate opening, plated cold-formed steel
	100% proof loaded to 3,600 lbs., minimum tensile strength 5,000 lbs.
	100% gate loaded to 3,600 lbs.
<b>Webbing</b>	1" nylon, minimum tensile 6,000 lbs.
<b>Thread</b>	White Polyester Nubond

### PERFORMANCE SPECIFICATIONS

<b>Lanyard Class</b>	Restraint/Positioning Only
<b>ANSI User Capacity</b>	130-310 lbs.
<b>OSHA User Capacity</b>	400 lbs.

### RELEVANT STANDARDS

<b>ANSI</b>	Z359.3
<b>OSHA</b>	Meets or exceeds all OSHA requirements

### SIZES/LENGTHS

<b>6' standard length additional lengths may be available</b>
---

### Notes

--