



# PRODUCT SPECIFICATIONS

## 631-DL-KIT

### Product Description:

This FrenchCreek harness kit comes with a full body harness, and dual-leg shock absorbing lanyard, and carry bag. A perfect setup for workers on the go. Ideal for general construction or roofing.

### Product Features:

- 3 point adjustment (chest and leg straps)
- Sliding back dorsal D-ring
- Lightweight, high strength synthetic webbing
- Dual leg lanyard for 100% tie-off
- Self-locking snaphook 3/4" gates



MATERIAL SPECIFICATIONS	
<b>Webbing</b>	1-3/4" polyester, min tensile strength 6,500 lbs.
<b>Hardware</b>	D-rings: plated alloy steel, powder coated, proof loaded to 3,600 lbs., min. tensile strength 5,000 lbs.
	Mating Buckles: Plated alloy steel, powder coated, spring loaded
	Z74 Snaphook 3/4" gate opening, plate cold-formed steel
	100% proof loaded to 3,600 lbs, min tensile strength 5,000 lbs.
	100% gate loaded gate loaded to 3,600 lbs.
<b>Padding</b>	STRATO-Lite air mesh comfort padding

MATERIAL SPECIFICATIONS	
<b>OSHA User Capacity</b>	400 lbs.
<b>ANSI User Capacity</b>	130 to 310 lbs.
<b>Lanyard Class</b>	6' free fall
<b>Arrest Force</b>	900 lbs

RELEVANT STANDARDS	
<b>ANSI</b>	ANSI Z359.1
<b>OSHA</b>	Meets or exceeds all OSHA requirements

SIZES/LENGTHS	
S-M, M-XL	
Lanyard length 6'	