## 650 Full Body Harness

## **Product Description**

The 600 series harnesses incorporate a lightweight design that will give your workers the freedom of movement when working from height.

## **Product Features**

- Adjustable shoulder, chest and leg straps
- Sub-pelvic strap
- Siding Back D-ring
- Lanyard retaining rings
- · Lightweight, synthetic webbing

MATERIAL SPECIFICATIONS	
Webbing	1-3/4" polyester webbing, minimum tensile strength 6,000 lbs.
Hardware	D-rings: plated alloy steel proof loaded to 3,600 lbs.
	min tensile strength 5,000 lbs.
	Mating Buckles: plated alloy steel, min tensile strength 4,000 lbs.
	Friction Buckles: plated alloy steel, min tensile strength 4,000 lbs.
	Tongue Buckles: forged steel, min tensile 4,000 lbs.
	Grommets: #2 Brass spur washer and grommet

PERFORMANCE SPECIFICATIONS		
ANSI User Capacity	130 to 310 lbs	
OSHA User Capacity	400 lbs	

RELEVANT STANDARDS		
ANSI	ANSI Z359.11-2014	
ANSI	Meets or exceeds all OSHA requirements	

## SIZES/LENGTHS

XS, S, M, L, XL, 2XL, 3XL



100 N 13th St. • Franklin PA • 16323 877.228.9327 • 814-437-1808 frenchcreekproduction.com **WARNING:** Read, understand and follow all labels and instructions prior to use, Inspect before each use. Remove from service if there is evidence of damage or excessive wear

REV: A DATE: 11/18/2020 PAGE: 1