



# PRODUCT SPECIFICATIONS

## 440AS Shock Absorbing Lanyard

### Product Description:

This dual-leg tubular-elastic web lanyard with shock absorbing pack limits fall arrest forces to 900 lbs. when tested to OSHA and ANSI standards.

### Product Features:

- 1-3/16" synthetic webbing with shock pack
- Stretches to minimize tripping and snagging hazards
- Standard 6' length relaxes to 4.5' when not stretched
- Z74 locking snaphooks on each end (3/4" gate opening)
- Additional Snaphook Options Available



MATERIAL SPECIFICATIONS	
<b>Hardware</b>	Z74 Snap hooks: 3/4" gate opening, plated cold-formed steel
	100% proof loaded to 3600 lbs min. tensile 5000 lbs
	100% gate loaded to 3600 lbs
<b>Webbing</b>	1-3/16" polyester webbing, min tensile strength 6,000 lbs.
	1-3/4" tear-away
<b>Core</b>	1" Elastic Cord

MATERIAL SPECIFICATIONS	
<b>Lanyard Class</b>	6' free fall
<b>Arrest Force</b>	900 lbs.
<b>ANSI User Capacity</b>	130 to 310 lbs.
<b>OSHA User Capacity</b>	400 lbs.

RELEVANT STANDARDS	
<b>ANSI</b>	ANSI Z359.1
<b>OSHA</b>	Meets or exceeds OSHA requirements

SIZES/LENGTHS
Standard length 6' additional sizes may be available.