

651H

Product Description:

The 600 series harnesses incorporate a lightweight design that will give your workers the freedom of movement when working from height.

Product Features:

- Adjustable chest and leg straps
- Sub-pelvic strap
- Sliding Back D-ring
- · Lightweight, synthetic webbing
- Chest mounted positioning D-ring

MATERIAL SPECIFICATIONS		
Webbing	1-3/4" polyester webbing, minimum tensile strength 6,000 lbs.	
Hardware	D-rings: plated alloy steel proof loaded to 3,600 lbs.	
	min tensile strength 5,000 lbs.	
	Mating Buckles: plated alloy steel, min tensile strength 4,000 lbs.	
	Tongue Buckles: forged steel, min tensile 4,000 lbs.	
	Grommets: #2 Brass spur washer and grommet	



MATERIAL SPECIFICATIONS		
ANSI User Capacity	130 to 310 lbs	
OSHA User Capacity	400 lbs	

RELEVANT STANDARDS	
ANSI	ANSI Z359.1
OSHA	Meets or exceeds all OSHA requirements

SIZES/LENGTHS

S-M, M-XL

WARNING: Read, understand and follow all labels and instructions prior to use. Inspect before each use. Remove from service if there is evidence of damage or excessive wear.

DATE 06/21/2023 **PAGE** 1

REV A