



PRODUCT SPECIFICATIONS

XR-7W Outlaw Self-Retracting Lifeline

Product Description

The Outlaw Series SRL's provide durability and confidence expected by professionals. All units feature lightweight housings, and short fall arrest capabilities

Product Features

- 7' synthetic webbing
- Class "1" SRL
- 3/4" opening snaphook
- 1" opening steel carabiner



MATERIAL SPECIFICATIONS

Lifeline Constituent	7' synthetic webbing
Housing/Hardware	Aluminum Housing
	Drum: Aluminum Alloy
	Ratchet Center & Brake Pawls: Brass
	Springs & Fastners: Stainless Steel
Lifeline Material	Ultra High Molecular Weight Polyethelene
Carabiner	Plated alloy steel, 3,600 lb. gate, Min tensile strength 5,000 lbs.
Snaphook	Plated alloy steel, 3,600 lb. gate, Min tensile strength 5,000 lbs.

PERFORMANCE SPECIFICATIONS

Arresting Force	Average arresting force 1350 lbs., Maximum arresting force 1,800 lbs.
Maximum Arrest distance	24 inches
OSHA Capacity	420 lbs.
ANSI Capacity	130-310 lbs.

RELEVANT STANDARDS

ANSI	ANSI Z359.14, A10.32 "Class 1" SRL
OSHA	Meets OSHA requiremenets

SIZES/LENGTHS

7' length
