

# PRODUCT SPECIFICATIONS

## 930B Full Body Harness

## **Product Description**

The 900 series can be used in a multitude of applications. The harness is donned by a step-thru procedure that is quick and easy.

#### **Product Features**

- Front cross-over style
- 4 point adjustment
- · Adjustable shoulder and leg straps
- Hip-positioning D-rings
- Chest D-rings for positioning, suspension and rescue
- Lightweight, high strength synthetic webbing

MATERIAL SPECIFICATIONS		
Webbing	1-3/4" polyester webbing, minimum tensile strength 6,000 lbs.	
Hardware	D-rings: plated alloy steel proof loaded to 3,600 lbs.	
	Min tensile strength 5,000 lbs.	
	Mating Buckles: plated alloy steel, min tensile strength 4,000 lbs.	
	Friction Buckles: plated alloy steel, min tensile strength 4,000 lbs.	

PERFORMANCE SPECIFICATIONS			
ANSI User Capacity	130 to 310 lbs		
OSHA User Capacity	400 lbs		

	RELEVANT STANDARDS
ANSI	ANSI Z359.11-2021
OSHA	Meets or exceeds all OSHA requirements

## SIZES/LENGTHS

XS, S, M, L, XL, 2XL, 3XL



