



# PRODUCT SPECIFICATIONS

## QL4107FB-18 Pacmule Firefighter Belt

### Product Description:

Our PacMule Firefighter Belts are specially designed multi-purpose tools that cater to the specific requirements of firefighters. These belts offer a perfect combination of lightweight design, exceptional quality, and high-performance capabilities.

### Product Features:

- Coolmax-lined comfort pad with
- 3M Scotchlite reflective material
- Patented drop-down tool D-rings with snap closures
- Forged front bailout ring
- Choice of quick release front snap



### MATERIAL SPECIFICATIONS

|                 |  |
|-----------------|--|
| <b>Webbing</b>  | 1-3/4" polyester (color varies), min tensile 6,000 lbs<br>(On -18 Models Only) 1" yellow web, min tensile 9,800 lbs.   |
| <b>Hardware</b> | Winged snap hook: plated alloy steel, proof loaded 5,000 lbs.<br>Adjuster D-ring: Zinc plated alloy steel, proof loaded 3,600 lbs.<br>min. breaking strength 5,000 lbs.<br>D-Ring : heat treated steel, zinc plated, proof loaded 3,600 lbs.<br>min breaking strength 5,000 lbs.<br>3" D-Ring : heat treated steel, zinc plated, proof loaded 3,600 lbs.<br>min breaking strength 5,000 lbs. |
| <b>Other</b>    | 3M scotchlite reflective material , 4 part button snap   |

### PERFORMANCE SPECIFICATIONS

|                           |    |
|---------------------------|----|
| <b>OSHA User Capacity</b> | NA |
| <b>ANSI User Capacity</b> | NA |
| <b>NFPA</b>               | NA |

### RELEVANT STANDARDS

|             |   |
|-------------|---|
| <b>ANSI</b> | NA  |
| <b>OSHA</b> | NA  |
| <b>NFPA</b> | Exceeds strength requirements for escape belts set forth by NFPA standard 1983/2017 edition |

### SIZES/LENGTHS

|                                       |
|---------------------------------------|
| S, M, L, XL, XXL (Use NFPA size chat) |
|---------------------------------------|