



PRODUCT SPECIFICATIONS

QN4105FB Pacmule Firefighter Belt

Product Description:

Our PacMule Firefighter Belts are specially designed multi-purpose tools that cater to the specific requirements of firefighters. These belts offer a perfect combination of lightweight design, exceptional quality, and high-performance capabilities.

Product Features:

- Coolmax-lined comfort pad with
- 3M Scotchlite reflective material
- Patented drop-down tool D-rings with snap closures
- Forged front bailout ring
- Choice of quick release front snap

MATERIAL SPECIFICATIONS

Webbing	1-3/4" polyester (color varies), min tensile 6,000 lbs (On -18 Models Only) 1" yellow web, min tensile 9,800 lbs.
Hardware	Winged snap hook: plated alloy steel, proof loaded 5,000 lbs. Adjuster D-ring: Zinc plated alloy steel, proof loaded 3,600 lbs. min. breaking strength 5,000 lbs. D-Ring : heat treated steel, zinc plated, proof loaded 3,600 lbs. min breaking strength 5,000 lbs. 3" D-Ring : heat treated steel, zinc plated, proof loaded 3,600 lbs. min breaking strength 5,000 lbs.
Other	3M scotchlite reflective material , 4 part button snap

PEFORMANCE SPECIFICATIONS

OSHA User Capacity	NA
ANSI User Capacity	NA
NFPA	NA

RELEVANT STANDARDS

ANSI	NA
OSHA	NA
NFPA	Exceeds strength requirements for escape belts set forth by NFPA standard 1983/2017 edition

SIZES/LENGTHS

S, M, L, XL, XXL (Use NFPA size chat)

