



PRODUCT SPECIFICATIONS

22442A Shock Absorbing Web Lanyard

Product Description:

This Dual-Leg Web Lanyard with pack style shock absorber limits fall arrest forces to 900 lbs. when tested to OSHA and ANSI standards.

Product Features:

- 1" synthetic webbing with shock pack
- Standard length 6, additional lengths available
- Additional snaphook options available



MATERIAL SPECIFICATIONS

Webbing	1" black nylon, minimum tensile strength 6000 lbs
	1 3/4" black polyester, minimum tensile strength 6000 lbs
Thread	Black bonded nylon
Hardware	69 snap-hook, 1 3/4" gate opening, forged plated steel
	100% proof loaded to 3600 lbs, minimum tensile 5000 lbs, gate loaded to 3600 lbs
	Z74 snap hook, 3/4" gate opening, cold plated steel
	100% proof loaded to 3600 lbs, minimum tensile 5000 lbs, gate loaded to 3600 lbs

PERFORMANCE SPECIFICATIONS

Lanyard Class	6" Free Fall
Arrest Force	900 lbs
ANSI User Capacity	130-310 lbs.
OSHA User Capacity	400 lbs.

RELEVANT STANDARDS

ANSI	ANSI Z359.13-2013
OSHA	Meets or exceeds all OSHA requirements

SIZES/LENGTHS

Standard length 6' additional sizes available
