



# PRODUCT SPECIFICATIONS

## 22450ASZ Shock Absorbing Web Lanyard

### Product Description:

This tubular-elastic web lanyard with shock absorbing pack limits fall arrest forces to 900 lbs. when tested to OSHA and ANSI standards.

### Product Features:

- 1-3/16" synthetic webbing with shock pack
- Stretches to minimize tripping and snagging hazards
- Standard 6' length relaxes to approximately 4.5' when not stretched
- Additional snaphook options available



MATERIAL SPECIFICATIONS	
<b>Webbing</b>	1 3/16" Polyester tubular webbing minimum tensile strength 6000 lbs.
	1 3/4" polyester tear-away
	1 3/4" black polyester, minimum tensile strength 6,000 lbs.
<b>Thread</b>	Polyester nubond
<b>Hardware</b>	#Z74 snap-hook: 3/4" gate opening, cold-formed plated steel
	100% proof loaded to 3,600 lbs min. tensile strength of 5,000 lbs

PERFORMANCE SPECIFICATIONS	
<b>Lanyard Class</b>	6" Free Fall
<b>Arrest Force</b>	900 lbs
<b>ANSI User Capacity</b>	130-310 lbs.
<b>OSHA User Capacity</b>	400 lbs.

RELEVANT STANDARDS	
<b>ANSI</b>	ANSI Z359.13-2013
<b>OSHA</b>	Meets or exceeds all OSHA requirements

SIZES/LENGTHS
Standard length 6' additional sizes available