



# PRODUCT SPECIFICATIONS

## 404A Shock Absorbing Rope Lanyard

### Product Description:

This polyblend rope lanyard with shock absorbing pack limits fall arrest forces to 900 lbs. when tested to OSHA and ANSI standards.

### Product Features:

- 1/2" diameter, three strand polyblend rope
- Standard length 6'
- Additional snaphook options available



### MATERIAL SPECIFICATIONS

<b>Material</b>	1/2" polyblend rope, minimum tensile strength 5,800 lbs.
	1-3/4" black polyester, minimum tensile strength 6,000 lbs
	1-3/4" polyester tear-away
<b>Hardware</b>	#Z74 snap-hook: 3/4" gate opening, zinc plated steel
	100% proof loaded to 3,600 lbs min. tensile strength of 5,000 lbs
	#Z136 Snap-hook, 2-1/2" gate opening, zinc plated steel
	100% proof loaded to 3,600 lbs min. tensile strength of 5,000 lbs

### PERFORMANCE SPECIFICATIONS

<b>ANSI User Capacity</b>	130-310 lbs. Max
<b>OSHA User Capacity</b>	400 lbs. Max
<b>Arrest Force</b>	900 lbs

### RELEVANT STANDARDS

<b>ANSI</b>	ANSI Z359.1-2007
<b>OSHA</b>	Meets or exceeds all OSHA requirements

### SIZES/LENGTHS

Standard length 6 ft, other lengths available.  
Item weight 2.74 lbs