



PRODUCT SPECIFICATIONS

444AB Shock Absorbing Web Lanyard

Product Description:

This adjustable Dual-Leg web Lanyard with pack style shock absorber limits fall arrest forces to 900 lbs. when tested to OSHA & ANSI standards.

Product Features:

- 1" Polyester webbing with shock pack
- Adjustable lanyards ordered by longest length
- Adjust down to approximately 2/3 length
- Additional snap-hooks available



MATERIAL SPECIFICATIONS

Hardware	Z74 snap hook, 3/4" gate opening, plated alloy steel
	100% proof loaded to 3,600 lbs min. tensile 5,000 lbs
	Z136 Snap-hook, 2-1/2" gate opening, plated alloy steel
	100% proof loaded to 3,600 lbs, min. tensile 5,000 lbs
	N-452L adjusters, zinc plated steel, min tensile strength 5,000 lbs
Webbing	1" yellow polyester, minimum tensile strength 9,800 lbs
	1-3/4" black polyester, minimum tensile strength 6,000 lbs
	1-3/4" tear away
Thread	Polyester nubond

PERFORMANCE SPECIFICATIONS

ANSI User Capacity	130-310 lbs.
OSHA User Capacity	400 lbs.
Arrest Force	900 lbs
Lanyard Class	6' Free Fall

RELEVANT STANDARDS

ANSI	ANSI Z359.13.2013
OSHA	Meets or exceeds all OSHA requirements

SIZES/LENGTHS

- Standard length 6', additional lengths available
- Item weight 4.6 Lbs.