



PRODUCT SPECIFICATIONS

444AS-135A Shock Absorbing Web Lanyard

Product Description:

The dual-leg tubular-elastic web lanyard with shock absorbing pack limits fall arrest forces to 900 lbs. When tested to OSHA and ANSI standards.

Product Features:

- 1-3/16" synthetic webbing with shock pack
- Stretches to minimize tripping and snagging hazards
- Standard length 6', additional lengths available
- Additional snaphook options available
- Elastic Core



MATERIAL SPECIFICATIONS

Hardware	Z74, 3/4" gate opening alloy steel locking rebar snap
	100% proof loaded to 3,600 lbs min. tensile 5,000 lbs
	100% gate loaded to 3,600 lbs
	#135A Aluminum snap-hooks, 2-1/2" gate opening
	100% proof loaded to 3,600 lbs, min. tensile 5,000 lbs
Webbing	1-3/16", yellow polyester, minimum tensile strength 6,000 lbs
	1-3/4" black polyester, minimum tensile strength 6,000 lbs
	1-3/4" tear away
Thread	Polyester nubond

PERFORMANCE SPECIFICATIONS

ANSI User Capacity	130-310 lbs.
OSHA User Capacity	400 lbs.
Arrest Force	900 lbs
Lanyard Class	6' Free Fall

RELEVANT STANDARDS

ANSI	ANSI Z359.13.2013
OSHA	Meets or exceeds all OSHA requirements

SIZES/LENGTHS

- Standard 6' length relaxes to 4.5' when not stretched
- Item weight 4.8 Lbs.