



# PRODUCT SPECIFICATIONS

## 444ASZ Shock Absorbing Web Lanyard

### Product Description:

This dual-leg tubular-elastic web lanyard with shock absorbing pack limits fall arrest forces to 900 lbs. when tested to OSHA and ANSI standards.

### Product Features:

- 1-3/16" Polyester tubular webbing with shock pack
- Stretches to minimize tripping and snagging hazards
- Standard length 6', additional lengths available
- Standard 6' length relaxes to 4.5' when not stretched
- Additional snaphook options available



### MATERIAL SPECIFICATIONS

<b>Hardware</b>	Z74 snap hook, 3/4" gate opening, zinc plated steel
	100% proof loaded to 3,600 lbs min. tensile 5,000 lbs
	100% gate loaded to 3,600 lbs
	Z136 Snap-hooks, 2-1/2" gate opening zinc plated steel
	100% proof loaded to 3,600 lbs, min. tensile 5,000 lbs
	100% gate loaded to 3,600 lbs
<b>Webbing</b>	1-3/16" yellow tubular polyester min tensile strength 6,000 lbs
	1-3/4" black polyester, 1-3/4" tear away
<b>Thread</b>	Polyester nubond

### PERFORMANCE SPECIFICATIONS

<b>ANSI User Capacity</b>	130-310 lbs.
<b>OSHA User Capacity</b>	400 lbs.
<b>Arrest Force</b>	900 lbs
<b>Lanyard Class</b>	6' Free Fall

### RELEVANT STANDARDS

<b>ANSI</b>	ANSI Z359.13.2013
<b>OSHA</b>	Meets or exceeds all OSHA requirements

### SIZES/LENGTHS

Standard length 6'  
Item weight 6.05 Lbs.