



# PRODUCT SPECIFICATIONS

## 450A-3 Shock Absorbing Web Lanyard

### Product Description:

This web lanyard with pack style shock absorber limits fall arrest forces to 900 lbs. when tested to OSHA and ANSI standards.

### Product Features:

- 1" synthetic webbing with shock pack
- Standard length 3', additional lengths available
- Two self-locking snaps at each end (3/4" gates)
- Additional snaphook options available

### MATERIAL SPECIFICATIONS

<b>Webbing</b>	Yellow 1" nylon, tensile strength 6,000 lbs.
	1-3/4" black polyester, minimum tensile strength 6,000 lbs
	1-3/4" polyester tear-away
<b>Hardware</b>	#Z74 snap-hooks: 3/4" gate opening, zinc plated steel
	100% proof loaded to 3,600 lbs min. tensile strength of 5,000 lbs
<b>Thread</b>	Polyester nubond



### PERFORMANCE SPECIFICATIONS

<b>ANSI User Capacity</b>	130-310 lbs. Max
<b>OSHA User Capacity</b>	400 lbs. Max
<b>Arrest Force</b>	900 lbs

### RELEVANT STANDARDS

<b>ANSI</b>	ANSI Z359.13-2013
<b>OSHA</b>	Meets or exceeds all OSHA requirements

### SIZES/LENGTHS

Standard length of 3 Feet.