



PRODUCT SPECIFICATIONS

454AB Shock Absorbing Web Lanyard

Product Description:

This adjustable web lanyard with pack style shock absorber limits fall arrest forces to 900 lbs. when tested to OSHA & ANSI standards.

Product Features:

- 1" synthetic webbing with shock pack
- Adjust down to approximately half the length
- Standard length of 6'
- Additional snaphook options available

MATERIAL SPECIFICATIONS

Hardware	Z74 Snap hook: 3/4" gate opening plated alloy steel
	100% proof loaded to 3,600 lbs, min. tensile 5,000 lbs
	100% gate loaded to 3,600 lbs
	Z136 Locking snap hook 2-1/2" gate opening plated alloy steel
	proof loaded to 3,600 lbs, min tensile strength 5,000 lbs
	N-452L Adjuster, zinc plated steel, min tensile strength 5,000 lbs
Webbing	1" yellow nylon webbing, minimum tensile strength 9,800 lbs
	1-3/4" polyester, minimum tensile strength 6,000 lbs
	1-3/4" tear-away
Thread	White polyester nubond

PERFORMANCE SPECIFICATIONS

ANSI User Capacity	130-310 lbs. Max
OSHA User Capacity	400 lbs. Max
Arrest Force	900 lbs
Lanyard Class	6' Free Fall

RELEVANT STANDARDS

ANSI	ANSI Z359.13-2013
OSHA	Meets or exceeds all OSHA requirements

SIZES/LENGTHS

Standard length 6' additional sizes available.
Adjustable lanyards ordered by longest length
Item weight 3 lbs

